


PIN ASSIGNMENT

A (IEEE 1394b 9M) (IEEE 1394b 9M)



B



- 1 綠 GREEN
- 2 紅 RED
- 3 橙 ORANGE
- 4 藍 BLUE
- 5 DRAIN WIRE
- 6 黑 BLACK
- 8 白 WHITE
- SHELL SHELL

①	IEEE 1394b BETA CONNECTOR, 9 PIN, INSULATOR COLOR: BLACK	2
②	PVC MOLDING HOUSING, COLOR: BLACK	2
③	PVC MOLDING THUMB SCREW M3.0, COLOR: BLACK	4
④	ASSEMBLY FERRITE CORE, COLOR: BLACK	2
⑤	IEEE 1394b CABLE, UL20276 25AWG*2 TWISTED PAIRS+22AWG*2 CONDUCTORS, DOUBLE SHIELDED, PVC JACKET, COLOR: GRAY	1

<p>展勝電業製品廠 SURE-FIRE ELECTRICAL MANUFACTORY</p>		IEEE 1394b CABLE	
		P/N	F1870C-0450-GE
CUSTOMER P/N		DWG	F1870C
CUSTOMER		REV	1.0
UB		TOLERANCES: .X=±.25 .X=±.05	
SCALE: 1/1		UNIT: mm	
DRAWN	CHECKED	APPROVED	DATE
劉三光			DEC.28.2005